



SHIELDFLEX SPRINKLER DROP

Save time! Save labor! Save money!

SHIELDFLEX Sprinkler Drops are designed to significantly reduce labour and installation costs. Available in 5 different lengths with 1/2" or 3/4" NPT on reducer thread.

Technical Data Unbraided Model: SDF-N, UL / ULC Listed

reclinical bata officialded Model. 3DI -N, 0L7 OLC Listed						
Temprature	225°F / 107°c					
Working Pressure	175 psi					
Connection	Inlet	1" NPT / BSPT				
Connection	Outlet	1/2" or 3/4" NPT				
Maximum Bend Radius	*Do not bend within 2.52 inches from the connection nuts.					
Maximun Number of Bend	Refer to Friction Loss Data					
K- Factor	1/2" Outlet	5.6 gpm				
N- I actor	3/4" Outlet	14.0 gpm				
Bending angles(flow direction)	Up to 180 degree					
Length in mm	700, 1000, 1200, 1500 & 1800					



Unbraided Flexible Tube

Technical Data Braided Model: SDF-B, UL / ULC / FM Listed

225°F / 107°c						
200 psi						
Inlet	1" NPT / BSPT					
Outlet	1/2" or 3/4" NPT					
*Do not bend within 2.52 inches from the connection nuts.						
Refer to Friction Loss Data						
1/2" Outlet	5.6 gpm					
3/4" Outlet	14.0 gpm					
Up to 180 degree						
700, 1000, 1200, 1500 & 1800						
	200 psi Inlet Outlet *Do not bend within 2 Refer to 1/2" Outlet 3/4" Outlet Up to 180 degr					

Inlet Nipples



Bottom Up Reducer



Center Brackets



Square Bar




Features

Intended use: Wet and Dry System

Wing Brackets





Friction Loss Data

Length (mm)	Outlet Connection	Maximum Number of 90° Bends	Minimum Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 pipe, (C=120),ft
700	1/2"	1	6	12
	3/4"	1	6	17
1000	1/2"	1	6	43
	3/4"	1	6	53
1200	1/2"	2	6	65
	3/4"	2	6	22
1500	1/2"	2	6	35
	3/4"	2	6	39
1800	1/2"	2	6	47
	3/4"	2	6	53

^{*} SHIELD reserves the right to change the contents without notice

UK Operation

Redburn House, 2a Tonbridge Road

Romford, Essex - RM3 8QE United Kingdom.

Tel: +44 (0) 1708377731 Fax: +44 (0) 1708347637 E-mail: shielduk@shieldglobal.com

Regional office for Middle East & Africa

Jebel Ali Free Zone Dubai,

United Arab Emirates TEL: +971 (4) 8812070 Fax: +971 (4) 8812198

Email: shieldme@shieldglobal.com