

INDICATOR POST

MODEL: SD-800W

- Used for application where a valve is install behind a wall
- The wall flange of the wall type indicator post is tapped for 4" schedule 40 steel pipe which extends through the wall
- Handwheel operation
- Compactable to be used with supervisory switches

| PART NAME | MATERIAL | ASTM SPEC. |
|----------------|-----------------|---------------|
| Body | Cast Iron | ASTM A126-B |
| Cap | Cast Iron | ASTM A126-B |
| Socket | Cast Iron | ASTM A126-B |
| Cotter Pin | Stainless Steel | AISI 304 |
| Hex. Head Bolt | Steel | ASTM A307-A |
| Extension Rod | Mild Steel | A105-80 |
| Hexagon Nut | Steel | ASTM A307-A |
| Target Frame | Cast Bronze | ASTM B62 |
| Window Glass | Plexi Glass | |
| Operating Stem | Cast Bronze | ASTM B62 |
| Retaining Ring | Steel | SAE 1065-1090 |
| Handwheel | Cast Iron | ASTM A126-B |
| Sign Plate | Aluminium | |
| Washer | Steel | Commercial |
| Window Frame | Steel | Commercial |

| Nominal Size | Extension Rod Length | Dimensions in Inches | | Weight Lbs |
|--------------|----------------------|----------------------|-------|------------|
| | | 4" | 6" | |
| 4" | 3' | 9.56 | 13.63 | 90 |
| 6" | 3' | 13.69 | 18 | |
| 8" | 3' | 16.5 | 21 | |
| 10" | 3' | 19.88 | 24.63 | |
| 12" | 3' | 23.5 | 28.25 | |

