

ABC DRY POWDER PORTABLE FIRE EXTINGUISHERS

FEATURES

- Mono-ammonium phosphate based dry chemical agent.
- Capable of fighting Class A, B, C and E fires.
- Kitemark certified to BS EN3.
- Cylinders compliance to council directive 97/23/EC (PED) and Statutory instrument 1999 No.2001 is certified by BSI (0086).
- High quality polyester paint.
- Controlled discharge.
- Brass nickel plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique colour coded handle and base (optional).
- Rechargeable and easy to service.
- Choice of capacity from 1 to 12 Kg.




IDEAL USE

Houses, office, buildings, warehouses, farms, wood working area etc.

*NOTE

Not recommended for use on expensive and delicate equipment like computers, etc.

Model Number	SDP1	SDP2	SDP4	SDP6	SDP9	SDP12
Extinguisher Capacity	1 Kg	2 Kg	4 Kg	6 Kg	9 Kg	12 Kg
Propellant	95% Nitrogen + 5% Helium					
Fire Rating	8A 34B	13A 70B	21A 113B	34A 183B	43A 233B	55A 233B
Working Pressure	14 Bar	14 Bar	15 Bar	15 Bar	15 Bar	15 Bar
Maximum Operating Pressure	18.5 Bar @ 60°C					
Test Pressure	30 Bar					
Total Weight	2.0 Kg	3.7 Kg	7.5 Kg	10 Kg	14 Kg	17.8 Kg
Range of Discharge	4-5m	5-7m	7-8m	6-8m	6-8m	6-8m
Duration of Discharge	7-9 sec	10-12 sec	13-15 sec	18-20 sec	22-24 sec	28-30 sec
Hose Length with Nozzle	N/A	N/A	457mm	534mm	534mm	617mm
Operating Temperature	-20°C to +60°C					
Cylinder Material	CRCA Steel					
Height x Diameter (mm)	365 x 75	385 x 110	408 x 150	520 x 150	515 x 185	620 x 185



1. Valve / Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. Discharge Hose
6. Syphon Tube
7. Hose Holder
8. Discharge Nozzle
9. PVC Base

