



ACCESS PANEL

Access Doors feature sleek Door Design adding aesthetics, durability and robustness into a single design and are designed to cater in numerable access needs. These doors offer a wide range of flexible size, trim and core options. Access Doors are designed to give easy access to plumbing, mechanical and electrical fixtures, which are required to be latent behind the wall structures to retain the aesthetics of the building.

KEY FEATURES

- Highly Economical and Ready to Install
- Cold Rolled Steel, Metallic Coated as per ASTM A 792 Standard offering Superior corrosion resistance
- Door Core: Kraft Honeycomb Core / Rockwool
- Fully Flush Sleek Design
- Suitable for Plaster / Dry Wall
- Flanges: Exposed (or) unexposed
- Flush Continuous Piano Hinge / Concealed Pin Hinge
- Self-Closing and Self-Latching
- Fire Integrity: up to 120* Minutes Fire Integrity
- Temperature Rise Rating upto 650°F @ 30 minutes on unexposed face of the Door
- Tested to UBC 7-2, ANSI/UL 10B (or) BS 476 Part 22 Standard
- Sound Transmission Class: upto STC 38 (Operable)
- Thermal Characteristics: U Factor upto 0.7, R Factor upto 1.42
- Factory Powder Coated

AVAILABLE OPTIONS

- Base Material Options – Hot Dip Metallic Coated Cold Rolled Steel as per ASTM A 792 Standards
- Finish Options – Wood Finish
- Non Fire Rated / Non-Temperature Rated option available
- Design Option - Recessed Panel for cladding

INDICATIVE SIZE SELECTION CHART

(All Sizes in Inches - Width x Height basis)

Width	Height		
10"	10"	12"	18"
12"	12"	18"	24"
18"	18"	24"	48"
24"	24"	48"	