

SHIELD A-XT

NEW!



Extinguishant Control Panel

Shield A-XT is a new generation extinguishant releasing panel which is UL,FM listed

The simple, programmable configuration options and easy to install construction make Shield A-XT panels the ideal choice for small to medium sized systems using all extinguishant agents.



Programmable Functions

Access Level 2

- ❑ Test Zones 1 to 3
- ❑ Disable Zones 1 to 3
- ❑ Disable 1st Stage Alarms
- ❑ Disable Pre-activated 1st Stage Relay
- ❑ Disable Pre-activated 2nd Stage Relay
- ❑ Disable Extract Fan Output
- ❑ Disable Manual Release Input
- ❑ Disable Extinguishant Sub System
- ❑ Activate Extract Fan Output
- ❑ Activate Alarm Delays

Access Level 3

- ❑ Sounder Delay
- ❑ Coincidence Detection
- ❑ Disable Panel Features
- ❑ Zone Alarm Delays (Detectors)
- ❑ Zone Alarm Delay (Call Points)
- ❑ Configure Zone for I.S Barrier Use
- ❑ Zone Short Circuit Alarm
- ❑ Zone Non Latching
- ❑ Zone Inputs Delay
- ❑ Extinguishant Release Time Delay
- ❑ Extinguishant Release Duration Timer
- ❑ Extinguishant Reset Delay Timer

Features

- ❑ UL864 and FM listed
- ❑ Three initiation circuits as standard
- ❑ Any single zone or any combinations of zones can be configured to release
- ❑ Configurable first stage NAC delays
- ❑ Configurable detection delays
- ❑ Zero time delay upon manual release option
- ❑ Compatible with I.S. barriers
- ❑ Non-latching zone input option to receive signals from other systems such as aspirating equipment
- ❑ Configurable extinguishant delays up to 60 seconds in 5 second steps
- ❑ Configurable extinguishant duration up to 5 minutes in 5 second steps
- ❑ Countdown timer shows time remaining until release
- ❑ Supports up to seven, four wire status indicators
- ❑ Built in Extract Fan control

Product Overview

- ❑ Designed and manufactured to the highest standards in a quality controlled environment and with UL & FM approvals, the Shield A-XT releasing panel offers outstanding value and performance for all small to medium fixed firefighting installations
- ❑ With three detection zones as standard, extinguishant release can be configured to activate from any combination of detection zone inputs to allow (among other combinations) any two from three type activations such as would be required for detection in ceiling void, room and floor void applications.
- ❑ The extensive configuration options of the Shield A-XT allow the functionality of the system to be extensively modified
- ❑ The panel contains a large LED display to enable easy configuration and control which also displays the time remaining until extinguishant release for added user safety.
- ❑ The countdown timer is duplicated on up to seven remote status units to provide local indication of the system status.
- ❑ With all of the electronics mounted on a single, easily removable, steel plate Shield A-XT panels are both robust and easy to install.
- ❑ Shield A-XT is supplied in an enclosure that matches the design and colour of the elite RS range and is available in standard red or optional grey.

