

Emergency luminaire

Model No: X130HM

LED Hanging Mount Exit Luminaires are designed according to DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

Housing of the Luminaire is made up with Polycarbonate Material specifically for High Ceiling or Parking Areas.



TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Ceiling mounted
Viewing distance	20 m
Pictograph	Set
Housing material	Plastic
Colour	RAL 9003
Mechanical rating IP	65
Impact resistance IK	≥ 3
Protection class	2
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	single luminaire switching
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	3,6 W
Power consumption maintained	3,6 W
Power consumption non-maintained	1,1 W
Ambient temperature maintained mode	-20 °C / 50 °C
Ambient temperature non-maintained mode	-20 °C / 50 °C
Length	168 mm
Width	236 mm
Height	136 mm

Weight	0.87 kg
Weight incl. Packaging	0.87 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	None
Dimming function	Yes

TECHNICAL DRAWING

